

INDEX

- 3D plots
 - draping with image data, 4.58
 - of lakebed profile, 4.31
 - of mid-water targets and lakebed profile, 4.31
 - of water intake bays, 4.56
 - of vertical shaft, 4.28
- 3D side-scan, *see* interferometric (3D) side-scan
- above-water laser imagery, combining with scanning sonar images, 5.24
- absolute and relative XY grids, 4.17–4.18
- absorption, 1.31
- acoustic beam, geometric spreading of, 1.23
- acoustic coverage, 2.11–2.12
 - single-beam side-scan, 9.8
- acoustic footprint
 - of 1.7° conical beam, 4.17
 - vs. range, formula for, 4.63
 - size of, and incident angle, 4.16
- acoustic imaging, 1.5
- acoustic intensity, 1.21
- acoustic multipath, 1.37–1.41
 - factors affecting, 1.42
 - surface-generated, 1.38
- acoustic multiples, and surface returns, 3.43
- acoustic navigation, ROV body search pattern without, 8.29
- acoustic perspective, changing sonar position and, 5.42
- acoustic profiling
 - introduction to, 4.7–4.9
 - scanning sonar for, 4.7–4.72
- acoustic reflectivity, 1.25–1.31
- acoustic refraction, 1.32–1.34
 - due to vertical beam coverage, 3.42
 - halocline-induced, 1.37
- acoustic response of sea grass to LF and HF, 9.13
- acoustic roughness targets, and specular reflector, 1.30
- acoustic shadows, 1.12–1.17
 - and diver positioning, 6.15
 - geometry of, 1.16
 - and seabed depressions, 1.16
 - and target height, 1.16
 - and target interpretation, 1.15
- acoustic signal, 1.13
- acoustic spokes, due to current-induced head oscillation, 3.46
- acoustic tracking responder, 9.29
- acoustics, 1.7
 - concepts and terminology of, 1.8–1.47
 - underwater, overview of, 1.5–1.47
 - units of measurement for, 1.20–1.22
- adjacent scans, combining to create mosaic, 5.27
- Adobe Photoshop, image scaling in, 5.32
- A-frames, 9.60
- alignment, of targets, 9.49
- along-track resolution, *see* transverse resolution
- altimeter, deployment cage for, 4.51
- amplitude shading, 2.19
- angles, depression, transducer, 9.50
- antenna tower, deploying scanning sonar using, 4.37
- aperture, synthetic, side-scan sonar, 9.22–9.26
- aquatic plants, and body search and recovery, 8.15
- ARCNET, 2.44
- armoured cable depth and layback position, 9.28
- Asymmetric Digital Subscriber Line (ADSL), 2.44
- attenuation of sound
 - in fresh water at 4°C, 1.31
 - in saltwater at 4°C, 1.32
- automatic gain control (AGC), 3.60
- autonomous underwater vehicle (AUV), synthetic aperture side-scan, 9.23
- azimuth (yaw), 4.26–4.27
 - alignment, and ROVs, 7.11
- background noise, 3.60–3.61
 - checking for other active sonars, 3.56
 - rain-induced, 3.61
 - with system in operation, 3.57
- background reverberation, 1.46
 - from surface and mid-water targets, 1.47
- backhoe, spreader bar deployment to position bucket, 3.54
- backside radiation, 2.10–2.11
 - and incorrect profile points, 4.12
- banded returns, 3.37
 - and target smearing, 3.36
- bandwidth, 2.23–2.26
 - and long-range target detection, 2.29
 - and pulse length, 2.25, 2.26
 - and pulsed CW sonar range resolution, 2.32
 - receiver, 3.16
 - selection of, 3.62
 - and target definition, 2.27
- bar check, 4.25, 4.26
- baseline surveys, and mosaics, 5.40–5.42
 - dock survey, 5.43
- batwings, 4.40
 - current-stabilized, for cross-sectional riverbed profiles, 4.41
 - profile coverage from, 4.45
 - side-view rigging of, 4.42
 - swath profile coverage, plan view of, 4.44
 - upstream view of scan geometry, 4.43

- beam angle, 2.11
 - calculating, 2.14
 - effect on absolute depth measurement, 4.8
 - horizontal, 2.12
 - footprint coverage of, 3.33
 - impact on resolution, 2.11
 - vertical, 2.12
 - footprint coverage of, 3.41–3.42, 3.44
- beam coverage, multipulse side-scan, 9.20
- beam pattern
 - directivity of, concepts and approximations, 2.12–2.14
 - and step size, vs. bottom coverage, 3.36
- beam plots, one and two-way, 2.16–2.17
- beam propagation, effect of refraction on geometry of, 1.34
- beam spreading, incident angle, and target reflectivity, 1.29
- beams
 - 1.7° conical
 - acoustic footprint of, 4.17
 - incident angle vs. depth errors for, 4.16
 - fan
 - vs. narrow, for profiling, 4.7
 - profiling with, 4.30
 - nearfield and farfield focusing, 2.14–2.19
 - narrow vs. fan, for profiling, 4.7
 - narrow vertical
 - geometric consequence of using, 3.44
 - geometry of, 3.40
- beamwidth
 - vs. frequency, 2.13
 - one-way, 2.17
 - two-way, 2.17
 - vertical, 2.17–2.19
- bedrock, seabed mosaic showing, 9.47
- bending, of target, 3.30
- biomass, reverberation in mid-water target, 1.47
- bistatic system, 2.6
- bit rate, and signal quantization, 2.40
- boat launches, and body search and recovery, 8.14–8.15
- body search and recovery, 8.5–8.36
 - body detection on a benign bottom, 8.12
 - body located with high-frequency side-scan, 8.21
 - body on lake bed with multiple specular reflectors, 8.33
 - body size, clothing, and cause of death, 8.8–8.10
 - bottom conditions, 8.12–8.13
 - contacting local police authority, 8.8
 - equipment selection considerations, 8.5–8.7
 - high-frequency side-scan sonar record showing
 - a body, 8.6
 - interpreting the target, 8.30
 - local conditions in, 8.14–8.15
 - mounting the GPS for, 8.23
 - navigation requirements for, 8.16
 - observation-class ROV
 - body recovery, 8.36
 - scanning sonar search patterns, 8.26–8.28
 - questions to resolve prior to search, 8.7–8.15
 - rigging the scanning sonar cable, 8.23
 - scanning sonar drop deployment, 8.24–8.26
 - search based on corroborative evidence, 8.10
 - search patterns and methods, 8.20–8.30
 - size of search area, 8.10–8.11
 - target markers, 8.17–8.20
 - tripod deployment method, 8.22
 - tripod-deployed scanning sonar search
 - patterns, 8.21–8.23
 - use of divers for recovery, 8.32
 - use of observation-class ROV for recovery, 8.33–8.34
 - use of scanning sonar to locate body and other evidence, 8.7
 - use of side-scan and scanning sonar, 8.5–8.36
 - water depth, 8.11
- bottom
 - benign, body detection on, 8.12
 - complex, of Toledo Bend Reservoir, 8.13
 - conditions of, for body search and recovery, 8.12–8.13
 - single-beam speed over, 9.9
- bottom coverage, vs. step size and beam pattern, 3.36
- bottom gradients, observing first return to determine, 3.24
- bottom reverberation
 - isolating parasitic devices on ship hull from, 3.39
 - using tilt transducer to minimize, 3.38
- bottom scans, and vertical scans, correlation of, 5.18, 5.22–5.23
- bottom slope, effect on calculating target height, 3.25
- bottom targets
 - vs. mid-water targets, establishing, 6.14
 - surface returns potentially masking, 3.42
- bow-mount deployment, 3.44, 3.48, 3.50, 9.62
 - frame-deployed side-scan, 9.63
- box frame, deployment of, 5.10
- bracket-deployed side-scan visualization
 - of bridge pier, 5.8
 - of dock, 5.7
- bridge, dual-axis scanning sonar profiles of, 4.46
- bridge pier, 4.13
 - instability of side-scan sonar adjacent to, 5.9
 - pole-deployed scanning sonar profile of, 4.35
 - visualization of, with bracket-deployed side-scan, 5.8
- cable
 - armoured, depth and layback positions, 9.28
 - counter for, 9.40
 - depressors, 9.33–9.35
 - rigging of, 9.34
 - drum brakes for, 9.39
 - fairing, 9.33
 - hand-deployed, 9.27, 9.61–9.62
 - rigging, for body search and recovery, 8.23
 - speed of deployment and recovery, 9.38
 - tow
 - depth and layback positions, 9.28
 - grip arrangement to secure, 9.62
 - hand-deployed side-scan, 9.27
 - hand-deployed stern, 9.61

- winch-deployed, 9.32–9.33
- cabling, 2.5, 2.45
 - requirements for manned submersibles, 7.19
 - requirements for ROVs, 7.17–7.18
- cage, drop-deployed, with stabilization fin, 3.48
- camera, surveillance, 9.40
- central processing unit (CPU), 2.5, 2.22
- checks
 - pre-deployment, 3.54
 - surface operation, 3.54–3.55
- CHIRP
 - scanning sonar, 3.17
 - side-scan sonar, 9.17
 - “multipulse,” 9.19–9.20
 - range resolution, 9.17
 - records, 9.17, 9.18
 - transmission and resolution, 2.33–2.35
- clump weighting small ROV umbilicals, 7.28
- colour palettes
 - comparison of, 3.59
 - sample of, 3.58
 - selection of, 3.57–3.58
- compass
 - integrated, determining target magnetic bearing without, 8.26
 - heading, directing diver to target on, 8.34
- composite transducers, 2.9–2.10
- correlation, of bottom and vertical scans, 5.18, 5.22–5.23
- corrosion
 - head, 7.12
 - housing, and dissimilar metals, 7.11–7.12
- coverage
 - acoustic, single-beam side-scan, 9.8
 - batwing swath profile, plan view of, 4.44
 - contiguous scanning sonar, for mosaics, 7.25
 - with dual-head pipeline profiler, 4.67
 - echo sounder, with scanning sonar, 4.13
 - horizontal, 3.33, 3.34, 8.30
 - in horizontal pipeline and tunnel profiling, 4.61–4.62
 - internal pipeline and tunnel, 4.64
 - multibeam side-scan, 9.16
 - multipulse side-scan beam, 9.20
 - overlapping, 5.13, 5.19–5.20
 - tripod and drop sonar grid patterns, 8.24
 - from pole and batwing deployment systems, 4.45
 - profile, with scanning sonar, 4.9
 - search and survey grids, 9.56
 - and shadows, scanning sonar, 5.26–5.43
 - side-scan, calculating, 9.57
 - Z-swath, with scanning sonar, 4.14
- crab traps, used as target markers, 8.18
- cross-track resolution, *see* range resolution
- current, 6.10
 - current-induced head oscillation, acoustic spokes due to, 3.46
 - current-stabilized deployment systems, 4.40–4.43
 - patterns, and body search and recovery, 8.14
 - data, multipulse vs. single-beam side-scan, 9.21
 - data backup, 5.30
 - data collection, 9.64–9.68
 - to create mosaic, 5.29
 - data recording, 5.28, 9.41
 - in horizontal pipeline and tunnel profiling, 4.61
 - requirements, and ROVs, 7.20–7.21
 - davits, 9.60
 - decay time, 2.27
 - decibels, 1.21
 - declination, 4.25
 - deployment
 - arrangements, 3.44–3.54
 - to profile 24m-diameter vertical shaft, 4.50
 - bow-mount, 3.44, 3.48
 - frame-deployed side-scan, 9.63
 - box frame, 5.10
 - cable, speed of, 9.38
 - cage for scanning sonar and altimeter, 4.51
 - current-stabilized systems, 4.40–4.43
 - drop, for body search and recovery, 8.24–8.26
 - drop-cable, 3.44, 3.48
 - of dual-axis profiler, for surge tower survey, 4.54
 - mechanical, other arrangements for, 4.35–4.39
 - pole and batwing, profile coverage from, 4.45
 - pole-mount, 3.44, 3.49
 - scanning sonar
 - using antenna tower, 4.37
 - set to side-scan mode, 5.8
 - shallow-water, 9.63
 - spreader bar, 3.44, 3.50, 3.51, 3.52–3.53, 3.54
 - systems for internal pipeline survey, 4.60–4.61
 - Texas tower, of scanning sonar heads, 4.39
 - towfish equipment, 9.63–9.64
 - tripod, 3.8, 3.44, 3.45
 - for body search and recovery, 8.22
 - and head orientation, 6.10–6.11
 - universal deployment pole for profiling scanning sonar, 4.36
 - vertical visualization arrangements, 5.12
 - of wet/dry diving bell scanning sonar, 6.16
- depression angles, of transducers, 9.50
- depressors, cable, 9.33–9.35
 - rigging of, 9.34
- depth errors, vs. incident angle, for 1.7° conical beam, 4.16
- depth measurement, absolute, effect of beam and incident angle on, 4.8
- detection threshold, 1.22, 1.24
- directivity index, 1.22, 1.24
- disc transducer, 2.14
- displacement, of structure, fixed head orientation to accent, 5.15
- displays
 - integrated navigation and scanning sonar, 7.24
 - after inverting sonar head, 7.9
 - magnification of, 2.38
 - polar mode, 3.7

- position vs. geometric position, 3.28
- and ROV control van layout, 7.20
- sector mode, 3.8
- single-frequency, dual-channel, 9.10
- single-frequency, single-channel, 9.10
- ZOOM, 2.37
- distortion, slant range, 3.26–3.28
 - on sheet pile wall, 3.29
 - percentage of error, 3.30
 - pitch, roll, and yaw, images of, 3.22
- dive time, minimizing with scanning sonar, 8.35
- divers
 - augmenting with sonar, 5.6–5.10
 - directing, 6.12
 - to side of tripod, 6.13
 - to target on compass heading, 8.34
 - using sonar, 6.8–6.16
 - positioning of
 - and acoustic shadows, 6.15
 - when prosecuting small targets, 6.12
 - use of, for body recovery, 8.32
- diving
 - distance from active sonar, 6.6
 - and safety, 6.6–6.8
 - and sonar, 6.5–6.16
 - surface-supplied gear with hardwire communications, 6.9
 - using scanning sonar for planning dive, 6.5
- diving bell, wet/dry, scanning sonar deployment, 6.16
- dock
 - survey mosaic, baseline, 5.43
 - visualization of, with bracket-deployed side-scan, 5.7
- dockside water test, 3.55–3.57
- domed head, 3.14
 - oil-filled, thermal defocusing of, 3.15
- draft and squat, 4.23–4.24
- draping
 - 3D plot with image data, 4.58
 - imaging data onto cloud point projections, 4.57
- dredge hole, horizontal profiles of, 4.53
- drop deployment
 - cable, 3.44, 3.48
 - scanning sonar, for body search and recovery, 8.24–8.26
 - sonar grid patterns and overlap coverage, 8.24
- dual-axis profilers
 - bridge profiles from, 4.46
 - deployment for surge tower survey, 4.54
 - shipwreck survey, 4.57
- dual-channel, single-frequency display, 9.10
- dual-frequency pulsed CW scanning sonar, 3.17
- dual-frequency side-scan, 9.9, 9.11
 - simultaneous, 9.11–9.12
- dual-head profiling, 4.66–4.70
 - cabling considerations in, 4.70
 - data from, 4.68
 - installation offsets, 4.67–4.69
 - mechanical mounting considerations in, 4.70
 - operations in, 4.70
 - pipeline coverage with, 4.67
 - ROV pipeline data, 4.69
 - ROV setup, 4.68
- dynamic range, 2.39
 - in sampling resolution and dB, 2.40
- echo sounder
 - coverage with scanning sonar, 4.13
 - mode line spacing and orientation, 4.32–4.33
 - record of, with scanning sonar, 4.28
 - survey grid patterns, 4.32
- electrical safety, 6.7
 - in side-scan field operations, 9.7
- elevation, 4.20–4.21
- elongation, of target, 3.30
- environmental protection, of winch, 9.39
- equipment
 - securing, 9.48
 - selection of, for body search and recovery, 8.5–8.7
 - towfish, deployment of, 9.63–9.64
- errors
 - depth, vs. incident angle, for 1.7° conical beam, 4.16
 - target position, factors contributing to, 9.46
- Ethernet, 2.44
- exposed head, 3.14
- fairing, cable, 9.33
- fan beam vs. narrow beam for profiling, 4.7
- farfield beam, effect of, 2.14–2.19
- field operations
 - with side-scan sonar, 9.7–9.72
 - general, 9.42–9.47
 - system selection for, 9.8–9.26
 - procedures and directions for, 9.57–9.58
- field spares, 9.70–9.71
- file labeling, 5.30
- file organization, 5.28
- files, mosaic, calculating dimensions of, 5.36
- fin, stabilization, drop-deployed cage with, 3.48
- first return
 - effect of slope gradient on, 3.23
 - observing to determine bottom gradients, 3.24
- fish, profile points generated by, 4.29
- flotation collar, mid-water target image of, 7.16
- footprint, acoustic
 - of 1.7° conical beam, 4.17
 - vs. range, formula for, 4.63
 - size of, and incident angle, 4.16
- fore and aft scanning sonar, head alignment for, 4.47
- frame-deployed bow mount side-scan, 9.63
- frequency, 1.18, 1.20, 2.27, 3.16
 - acoustic response of sea grass to, 9.13
 - vs. beamwidth, 2.13
 - vs. reflectivity, 1.26

- and resolution, 2.21–2.22
 - vs. speed of sound, 1.19
 - and wavelength, 1.19
- gain
- automatic gain control (AGC), 3.60
 - gain-generated noise, time-varied, 3.61
 - system, setting, 3.59–3.60
 - time-varied, 2.41–2.42
 - compensation of, 2.42
 - using wrong factors, 2.43
 - geographic coordinates, creating mosaics using, 5.39–5.40
 - geographic north vs. magnetic north, 4.25–4.26
 - geographic positioning of target, 9.43–9.45
 - geometric consequence, of using narrow vertical beam, 3.44
 - geometric effect, of step size and target detection, 3.35
 - geometric position, vs. display position, 3.28
 - geometry, 3.16
 - batwing, upstream view of, 4.43
 - head, matching to sloping structures, 5.15
 - of narrow vertical beam patterns, 3.40
 - of profile, 4.15–4.17
 - for ROV tunnel profiling, 4.60
 - of scanning sonar, 3.21–3.44
 - slant range correction, 9.52
 - of tilt transducer, 3.37
 - transmit and receive, interferometric side-scan, 9.14
 - geo-referencing
 - equipment configuration for ROVs, 7.23
 - requirements for ROVs, 7.22
 - and ROV seabed mapping, 7.21–7.25
 - gimballed sonar head, 6.9
 - Global Positioning System (GPS), 1.6
 - mounting, for body search and recovery, 8.23
 - gradients
 - bottom, observing first return to determine, 3.24
 - slope, effect on first return, 3.23
 - Grand Traverse Bay Underwater Preserve (MI), 3.43
 - graphic recorders, 9.40–9.41
 - grid markers, turning off, 5.31
 - grid patterns
 - echo sounder survey, 4.32
 - search and survey, 9.55–9.56
 - grip arrangement to secure tow cable, 9.62
- halocline, 1.32
 - halocline-induced acoustic refraction, 1.37
- hand-deployed cable, 9.61–9.62
 - stern tow, 9.61
 - options for, 9.27
- hand-deployed tripod and surface rigging, 3.47
- hardwire communications, surface-supplied gear with, 6.9
- hazards
 - man-made, and towfish, 9.66
 - potential, identifying, 6.7
- heads
 - alignment of, 5.14–5.15
 - with fore and aft scanning sonar, 4.47
 - to imaging surface, determining, 3.23–3.24
 - for internal pipe inspection, 4.64
 - azimuth alignment, and ROVs, 7.11
 - corrosion of, 7.12
 - domed, 3.14
 - oil-filled, thermal defocusing of, 3.15
 - exposed, 3.14
 - fixed orientation, 5.15
 - four, trencher profile system utilizing, 4.72
 - gimballed, 6.9
 - inverting sonar, and resulting display, 7.9
 - micro, 3.17, 3.19
 - normal to vertical structure, 3.16
 - orientation of
 - matching geometry to sloping structures, 5.15
 - reflective marker to determine under ice, 8.25
 - for scanning sonar, 4.46
 - and tripod deployment, 6.10
 - using waterline, 4.49
 - oscillation of, current-induced, 3.46
 - positioning, for ROVs, 7.6–7.7
 - powering, 7.19
 - requirements for horizontal pipeline and tunnel profiling, 4.59–4.60
 - Texas tower deployment of, 4.39
- high current, pole-deployed scanning sonar in, 4.34
- high frequency
 - acoustic response of sea grass to, 9.13
 - arrays, effect of towfish pitch on, 9.32
- high-frequency side-scan sonar record showing a body, 8.6
- HISAS side-scan, Hugin 1030 fitted with, 9.25
- historical knowledge, 9.59
- horizontal coverage
 - of 0.5° beam, 3.33
 - of 0.75° beam, 3.33
 - of 0.9° beam, 3.34
 - of 1.4° beam, 3.34
 - of 1.7° beam, 3.34
- horizontal drift, profile of, 4.52
- horizontal excursion coverage, 8.30
- horizontal image, of oil well gas leak, 3.11
- horizontal pipeline and tunnel profiling, 4.58–4.65
- horizontal profiles
 - of dredge hole, 4.53
 - of trash rack, 4.52
- horizontal shaft, point cloud data of, 4.55
- horizontally mounted imaging sonar, 7.16
- horizontally mounted scanning sonar
 - detailing vertical structures, 3.10
 - oil platform images using, 7.17
 - for pipeline imaging, 3.12
 - for ROVs, 7.15–7.17
 - search pattern, 7.15
 - submerged trees imaged with, 3.13

- housing corrosion, and dissimilar metals, 7.11–7.12
- Hugin 1030 fitted with HISAS side-scan, 9.25
- hull mounting, 9.62
- hydrophone, 2.6
- ice-covered surface, and body search and recovery, 8.15
 - shallow-water refraction and reverberation, 8.16
- image data, draped onto 3D plot, 4.58
- image scaling, 5.32–5.33
 - in Adobe Photoshop, 5.32
 - pixel count 120 – 300 feet, 5.33
 - pixel count 20 – 50 metres, 5.33
 - pixel count 40 – 100 metres, 5.33
 - pixel count 60 – 150 feet, 5.33
- images
 - multipulse 300kHz/600kHz, 9.22
 - of oil platform, using horizontally mounted scanning sonar, 7.17
 - reversed, 3.31, 3.32
 - synthetic aperture sonar, 9.26
 - of WWII submarine, 9.25
- imaging operations
 - background noise in, 3.60–3.61
 - colour palette selection, 3.57–3.58
 - dockside water test, 3.55–3.57
 - pre-deployment checks, 3.54
 - selecting receiver bandwidth, 3.62
 - setting system gain, 3.59–3.60
 - surface operation check, 3.54–3.55
- imaging sonar
 - horizontally mounted, for mid-water target detection, 7.16
 - mounted on work- and observation-class ROVs, 7.14
 - options for, 3.20
 - pole-mount deployment for, 3.49
 - ROV mount considerations, 7.10
 - selection of, 3.13–3.19
 - underwater, overview of, 1.5
 - vertically and orthogonally mounted, 7.18
- imaging surface, determining head alignment to, 3.23–3.24
- incident angle
 - and beam angle, effect on absolute depth measurement, 4.8
 - and beam spreading, 1.29
 - vs. depth errors for 1.7° conical beam, 4.16
 - and size of acoustic footprint, 4.16
 - and target orientation, 1.28
 - and target reflectivity, 1.29
- instability, of side-scan sonar, adjacent to bridge piers, 5.9
- insurance policy, 9.21
- integrated navigation and scanning sonar display, 7.24
- interferometric (3D) side-scan sonar, 9.13–9.14
 - pole-mounted, 9.13
 - and processed bathymetric data, 9.15
 - transmit and receive geometry, 9.14
- key plan, use of, 5.37
- kiting, towfish, 9.35
- lakebed profile, 3D plot of, 4.31
- large-diameter shaft survey, profiles from, 4.50
- laser imaging, 1.5
 - combining above-water imagery with sonar images, 5.24
- layback positions, for armoured and soft tow cable, 9.28
- layering, to maximize data resolution, 5.20
- legal ownership of targets, 9.59
- line pull, 9.38
- line turns, side-scan sonar, 9.58
- linear scaling, mosaic, 5.35
- linear transducer, 2.14
- logistical support, onsite, for body search and recovery, 8.15
- longitudinal waves, 1.10, 1.12
- low frequencies
 - acoustic response of sea grass to, 9.13
 - arrays, effect of towfish pitch on, 9.32
- magnetic bearing, determining without an integrated compass, 8.26
- magnetic north vs. geographic north, 4.25–4.26
- manned submersible, cable requirements for, 7.19
- manual range verification, 4.25
- mapping, seabed, ROV, and target geo-coding, 7.21–7.25
- marine traffic, and body search and recovery, 8.14
- match lines, use of, 5.37
- maximum response axis, 2.12
- measurement
 - metric drawing sizes, commonly used, 5.37
 - nautical mile conversions, 4.19
 - scale, creating, 5.35
 - units of, 4.19
 - acoustic, 1.20–1.22
 - US engineering drawing sizes, commonly used, 5.36
 - US Survey foot conversion factor, 4.19
- mechanical deployment arrangements, 4.35–4.39
- mechanical mount considerations, 4.70
 - for ROVs, 7.5–7.7
- mechanically scanned profiler
 - mounting of, 4.33
 - terminology for, 4.10–4.11
- merging different range scales, 5.34
- metal detecting, 1.5
- metals, dissimilar, and housing corrosion, 7.11–7.12
- metric drawing sizes, commonly used, 5.37
- micro heads, 3.17, 3.19
- mid-water targets
 - background reverberation from, 1.47
 - and body search and recovery, 8.15
 - vs. bottom targets, establishing, 6.14
 - detection with horizontally mounted imaging sonar, 7.16
 - images of rope and flotation collar, 7.16
 - reverberation of biomass, 1.47

- mode line spacing and orientation, of echo sounder, 4.32–4.33
- monostatic system, 2.6
- mosaics
 - baseline dock survey, 5.43
 - calculating file dimensions, 5.36
 - combining adjacent scans to create, 5.27
 - contiguous scanning sonar coverage for, 7.25
 - creating from multiple ranges, 5.21, 5.39
 - creating from scans with geographic coordinates, 5.39–5.40
 - data collection to create, 5.29
 - of downed oil platform, 5.40
 - getting started, 5.31–5.32
 - images recorded at different range settings, 5.37–5.39
 - linear scaling, 5.35
 - multi-drop, of oil rig wreckage, 5.41
 - of overlapping images collected at various ranges, 5.38 and positioning considerations, 5.28
 - scanning sonar, 5.24
 - search and survey requirements, 9.47
 - side-scan, seabed showing bedrock, 9.47
 - and structure baseline surveys, 5.40–5.42
- mounting
 - bow, 9.62
 - GPS, for body search and recovery, 8.23
 - hull, 9.62
 - imaging sonar, considerations for ROVs, 7.10
 - mechanical, considerations for ROVs, 7.5–7.7
 - of mechanically scanned profiler, 4.33
 - over-the-side, 9.62
 - scanning sonar, alternative arrangements for ROVs, 7.17
 - transducer, up/down, for ROVs, 7.7–7.9
 - vertical height, minimum, 7.7
- multibeam side-scan sonar
 - pulsed CW, 9.15
 - coverage, 9.16
 - record and towfish, 9.16
- multi-drop mosaic of oil rig wreckage, 5.41
- multipath
 - acoustic, 1.37–1.41
 - factors affecting, 1.42
 - in enclosed spaces, 1.45
 - surface, 1.39
 - side-scan, 1.40
 - thermocline-generated, 1.41
- multipulse side-scan
 - 300kHz/600kHz images, 9.22
 - CHIRP, 9.19–9.20
 - signal transmission, 9.19
 - vs. single-beam side-scan data, 9.21
- narrow beam vs. fan beam for profiling, 4.7
- narrow vertical beam
 - geometry of, 3.40
 - geometric consequence of using, 3.44
- nautical mile conversions, 4.19
- navigation
 - acoustic, ROV search pattern without, for body search and recovery, 8.29
 - for body search and recovery, 8.16
 - integrated with scanning sonar display, 7.24
 - receiver and transducer alignment, 4.33
 - requirements for side-scan sonar, 9.42
- neap tides, 4.22
- nearfield beam, effect of, 2.14–2.19
 - and tripod-deployed scanning sonar, 2.16
- Newton, 1.20
- noise, 3.16
 - acoustic, profile points generated by, 4.29
 - background, 3.60–3.61
 - checking for other active sonars, 3.56
 - rain-induced, 3.61
 - with system in operation, 3.57
 - gain-generated, time-varied, 3.61
 - noise level, 1.22
- observation-class ROVs
 - for body recovery, 8.33–8.34, 8.36
 - imaging sonar mounted on, 7.14
 - search patterns for body search and recovery, 8.26–8.28
 - trim of, 7.11
- obstacle avoidance sonar (OAS), 7.5
- offsets between sensors, 4.34
- oil platform
 - downed, mosaic of, 5.40
 - images using horizontally mounted scanning sonar, 7.17
 - multi-drop mosaic of wreckage, 5.41
- oil well gas leak, horizontal and plan images of, 3.11
- one-way beamwidth, 2.17
- onsite logistical support, for body search and recovery, 8.15
- orthogonally mounted imaging sonar, and vertically mounted, 7.18
- oscillation, head, current-induced, 3.46
- out-of-range returns, 1.42–1.44
 - side-scan, 1.44
 - geometry of, 1.43
- overlapping coverage, 5.13
 - seabed, 5.19–5.20
- overlapping images, collected at various ranges, 5.38
- over-the-side mounting, 9.62
- parasitic devices on ship hull, isolating from bottom reverberation, 3.39
- Pascal, 1.20
- piezocrystalline lead zirconate titanate (PZT), 2.6
- pile bent, visualization of, 5.17
- ping rate, 9.19
- pipelines
 - dual-head profiler coverage, 4.67
 - horizontal profiling, 4.58–4.65
 - coverage of, 4.61–4.62

- data recording in, 4.61
- equipment for, 4.59
- head requirements for, 4.59–4.60
- internal inspection head alignment, 4.64
- internal survey deployment systems, 4.60–4.61
- internal target resolution, 4.63
- position control in, 4.61
- ROV internal pipeline profiling, 4.64–4.65
- imaging of, horizontally mounted scanning sonar for, 3.12
- internal profile coverage, 4.64
- ROV dual-head profile data, 4.69
- synthetic aperture sonar image of, 9.26
- pitch, 3.21–3.22
 - and roll, 4.27–4.33
 - sensors for, 5.18
 - and roll and yaw alignment, 4.46–4.48
 - and roll, yaw, and XYZ orientation, 4.18
 - of towfish, 9.31
 - effect on high- and low-frequency arrays, 9.32
- plants
 - aquatic, and body search and recovery, 8.15
 - biomass, reverberation in mid-water target, 1.47
 - sea grass, acoustic response to frequencies, 9.13
- point cloud projections
 - 3D, of water intake bays, 4.56
 - data of surge tower and horizontal shaft, 4.55
 - draping imaging data onto, 4.57
 - of under-dock survey, 4.38
- polar mode display, 3.7
- pole deployment systems
 - for high current, 4.34
 - profile of bridge pier, 4.35
 - profile coverage from, 4.45
 - small vessel, 4.37
- pole-mount deployment, 3.44, 3.49
 - side-scan for vertical structure visualization, 5.6
 - interferometric side-scan, 9.13
- police, and body search and recovery, 8.8
- position control, in horizontal pipeline and tunnel
 - profiling, 4.61
- positioning
 - geographical, 9.43–9.45
 - and mosaics, 5.28
 - position, and acoustic perspective, 5.42
 - target errors, factors contributing to, 9.46
- power density, 1.21
- power output, effective, 2.23
- power ratios, in 3dB increments, table of, 1.22
- power source, for side-scan winch, 9.37–9.38
- power supply, 2.22
- pre-deployment checks, 3.54
- pressure, 1.20
- processed bathymetric data, and interferometric side-scan, 9.15
- processor, for side-scan sonar, 9.26
- profile points, 4.10
 - advantages and disadvantages in recording only, 4.10
 - generated by acoustic noise and fish, 4.29
 - generated from mid-water targets, 4.30
 - incorrectly generated by backside radiation, 4.12
- profilers
 - batwing, side-view rigging of, 4.42
 - dual-axis, deployment for surge tower survey, 4.54
 - dual-head
 - data from, 4.68
 - ROV setup, 4.68
 - mechanically scanned, mounting of, 4.33
 - second axis drive, 4.54–4.57
- profiles
 - batwing swath, plan view of coverage, 4.44
 - bridge, with dual-axis scanning sonar, 4.46
 - bridge pier, 4.13
 - coverage from pole and batwing deployment systems, 4.45
 - cross-sectional
 - riverbed, current-stabilized batwing for, 4.41
 - ROV alignment and distortion, 4.66
 - effects of unconsolidated slurry on data, 4.71
 - geometry of, 4.15–4.17
 - horizontal
 - of dredge hole, 4.53
 - of trash rack, 4.52
 - of horizontal drift, 4.52
 - lakebed, 3D plot of, 4.31
 - from large-diameter shaft survey, 4.50
 - overlaid, 4.53
 - pole-deployed, of bridge pier, 4.35
 - of rock shaft, 4.52
 - stacked, 4.53
 - survey basics, 4.21
 - under-dock, 4.38
 - vertical, of trash rack, 4.52
- profiling
 - acoustic, scanning sonar for, 4.7–4.72
 - deployment arrangement for 24m-diameter vertical shaft, 4.50
 - dual-head, 4.66–4.70
 - with fan beam, 4.30
 - fan beam vs. narrow beam for, 4.7
 - internal pipeline, with ROV, 4.64–4.65
 - mechanically scanned, terminology for, 4.10–4.11
 - narrow beam vs. fan beam for, 4.7
 - pipeline, horizontal, 4.58–4.65
 - pole-mount deployment for, 3.49
 - scanning sonar for, 4.9
 - trencher system utilizing four heads, 4.72
 - tunnel
 - horizontal, 4.58–4.65
 - ROV, geometry for, 4.60
 - underwater, survey basics, 4.15–4.27
 - universal deployment pole for scanning sonar, 4.36
 - vertical shaft, 4.49–4.54

- projector, 2.6
- propagation, velocity of, 1.17
- prosecution, of ROV scanning sonar target, 7.25–7.26
- pulse length, 2.23, 2.27, 3.16
 - for long-range target detection, 2.29
 - matched to 100kHz receiver bandwidth, 2.26
 - matched to 12kHz bandwidth, 2.25
 - for pulsed CW systems, 2.28
 - selecting, 2.28
- pulsed CW sonar
 - multibeam, side-scan, 9.15
 - range resolution, 2.32
- radiation, backside, 2.10–2.11
- rain-induced background noise, 3.61
- range
 - vs. acoustic footprint, formula for, 4.63
 - creating mosaic using different ranges, 5.21, 5.38, 5.39
 - manual verification of, 4.25
 - merging different scales, 5.34
 - mosaic images recorded at different settings, 5.37–5.39
 - multiple ranges, overlaying at one scan location, 5.34
 - scale, for towfish, 9.66
 - selection of, 9.50–9.54
 - and target size, 9.51
 - slant, and speed correction, 9.51–9.54
 - vs. transverse resolution, 4.63
 - vs. water depth, 3.40
- range 0, 4.20
- range errors, potential, 1.17
- range resolution, 2.30, 2.32–2.33
 - of CHIRP system, 9.17
 - pulsed CW sonar, 2.32
- raster images
 - converting to vector images, 5.26
 - overview of, 5.25–5.27
 - vs. vector images, 5.26
- ray trace plots, 1.33
- receivers, 2.38–2.40
 - bandwidth of, 2.23, 2.24, 3.16
 - selection of, 3.62
 - navigation, and transducer alignment, 4.33
- recorders
 - data, 9.41
 - graphic, 9.40–9.41
- recording
 - data requirements, and ROVs, 7.20–7.21
 - verification of, 5.30
- recordings
 - CHIRP side-scan, 9.17, 9.18
 - interpretation of, 9.71–9.72
 - multibeam side-scan, 9.16
 - slant range corrected, 9.53
- recovery/salvage operations, 6.16
- reflective marker, for under-ice head orientation, 8.25
- reflective surface, and beam pattern, 2.19
- reflectivity
 - acoustic, 1.25–1.31
 - vs. frequency, 1.26
 - of targets, 1.27
- reflectors
 - and acoustic roughness targets, 1.30
 - specular, 1.29
 - body on lake bed with multiple, 8.33
- refraction
 - acoustic, 1.32–1.34
 - due to vertical beam coverage, 3.42
 - effect on beam propagation geometry, 1.34
 - under-ice, 1.36
 - shallow-water, 8.16
- relative and absolute XY grids, 4.17–4.18
- remote control, of winches, 9.39
- resolution
 - along-track, 2.30, 9.9
 - CHIRP transmission and, 2.33–2.35
 - range of system, 9.17
 - comparison of samples, 5.19
 - cross-track, 2.30
 - and frequency, 2.21–2.22
 - layering scans to maximize, 5.20
 - range, 2.30, 2.32–2.33
 - pulsed CW sonar, 2.32
 - vs. transverse, 4.63
 - sampling, 2.35–2.36
 - transverse, 2.30, 2.31, 9.9
 - vs. range, 4.63
- responders, acoustic tracking, 9.29
- returns
 - banded, 3.37
 - and target smearing, 3.36
 - first
 - effect of slope gradient on, 3.23
 - observing to determine bottom gradients, 3.24
 - out-of-range, 1.42–1.44
 - smear, 3.37
 - surface
 - and acoustic multiples, 3.43
 - and acoustic refraction due to vertical beam coverage, 3.42
 - potentially masking bottom targets, 3.42
- reverberation
 - background, 1.46
 - from surface and mid-water targets, 1.47
 - of biomass, in mid-water target, 1.47
 - bottom
 - isolating parasitic devices on ship hull from, 3.39
 - using tilt transducer to minimize, 3.38
 - shallow-water, under-ice, 8.16
 - surface, using tilt transducer to reduce, 3.38
- reversed images, 3.31, 3.32
- revetment project, using spreader bar deployment, 3.51
 - overview of, 3.52

- rigging
 - cable depressor, 9.34
 - side-view, of batwing profiler, 4.42
 - surface float, 8.28
- rise time, 2.27
- riverbed profiles, cross-sectional, current-stabilized
 - batwing for, 4.41
- RLC-type filter, 2.45
- roll, 3.21–3.22
 - check for offset, 4.48
 - and pitch, 4.27–4.33
 - sensors for, 5.18
 - and pitch and yaw alignment, 4.46–4.48
 - and yaw, pitch, and XYZ orientation, 4.18
- rope, mid-water target image of, 7.16
- ROVs
 - alignment of, and cross-sectional profile distortion, 4.66
 - cabling requirements for, 7.17–7.18
 - clump weighting small umbilicals, 7.28
 - control van layout and displays, 7.19, 7.20
 - dual-head profiler
 - pipeline data, 4.69
 - setup, 4.68
 - equipment configuration to geo-reference target, 7.23
 - imaging sonar mount considerations, 7.10
 - mounting side-scan transducer on, 7.30
 - observation-class
 - for body recovery, 8.33–8.34, 8.36
 - imaging sonar mounted on, 7.14
 - search patterns for body search and recovery, 8.26–8.28
 - trim of, 7.11
 - requirements to geo-reference target, 7.22
 - scanning sonar, mechanical mount considerations, 7.5–7.7
 - search of steep slope, 8.32
 - search pattern without acoustic navigation,
 - for body search and recovery, 8.29
 - side-scan and scanning sonar, 7.5–7.30
 - side-scan deployed on, 7.29–7.30
 - tunnel profiling geometry, 4.60
 - work-class, imaging sonar mounted on, 7.14
- rub test, transducer, and transmit pulse, 3.55
- safety
 - diving, 6.6–6.8
 - electrical, 6.7
 - in side-scan field operations, 9.7
 - identifying potential hazards, 6.7
 - monitoring the worksite, 6.8
 - in side-scan field operations, 9.7
 - vessel, 6.7
- salvage/recovery operations, 6.16
- sampling resolution, 2.35–2.36
- sampling speed, 3.16
- scale range, for towfish, 9.66
- scan markers, turning off, 5.31
- scanning sonar
 - for acoustic profiling, 4.7–4.72
 - acoustic coverage of, 1.10
 - arrangement for tunnel inspection, 4.65
 - and backside radiation, 2.10
 - body search and recovery using, 8.5–8.36
 - bow-mounted, 3.50
 - CHIRP, 3.17
 - combining above-water laser imagery with images, 5.24
 - contiguous coverage for mosaics, 7.25
 - coverage and shadows, 5.26–5.43
 - coverage for tunnel inspection, 4.66
 - deployment
 - cage for, 4.51
 - using antenna tower, 4.37
 - directing diver with, 6.11–6.15
 - displays of, 1.11
 - for dive planning, 6.5
 - domed transducer head, 3.14
 - drop deployment, for body search and recovery, 8.24–8.26
 - dual-axis, bridge profiles, 4.46
 - dual-frequency pulsed CW, 3.17
 - echo sounder
 - coverage with, 4.13
 - record of, 4.28
 - and effect of thermocline refraction, 1.35
 - exposed transducer head, 3.14
 - fore and aft head alignment for, 4.47
 - geometry of, 3.21–3.44
 - head normal to vertical structure, 3.16
 - head orientation for, 4.46
 - horizontally mounted
 - detailing vertical structures, 3.10
 - oil platform images using, 7.17
 - for pipeline imaging, 3.12
 - for ROVs, 7.15–7.17
 - search pattern for, 7.15
 - submerged trees imaged with, 3.13
 - imaging operations with, 3.54–3.62
 - imaging system and options, 3.20
 - integrated navigation and sonar display, 7.24
 - internal pipeline and tunnel profile coverage, 4.64
 - minimizing dive time with, 8.35
 - mosaics, 5.24
 - mounting arrangements for ROVs, 7.17
 - mounting the GPS, 8.23
 - observation-class ROV, search patterns for body search and recovery, 8.26–8.28
 - and out-of-range returns, 1.45
 - overview of, 1.8–1.9
 - pole-deployed
 - in high current, 4.34
 - profile of bridge pier, 4.35
 - positioning target markers for, 8.19

- for profiling applications, 4.9
- range 0, 4.20
- rigged for drop deployment, 8.25
- rigging the cable, for body search and recovery, 8.23 and ROVs, 7.5–7.30
 - imaging sonar mount considerations, 7.10
 - mechanical mount considerations, 7.5–7.7
 - search patterns, 7.26–7.28
- set to side-scan mode, deployment of, 5.8
- shadows and coverage, 5.26–5.43
- and side-scan sonar, comparison of sub-structure inspection, 5.11
- in single-channel side-scan mode, 3.9
- single-beam pulsed CW, 3.14–3.17
- system selection for imaging applications, 3.13–3.19
- target prosecution, 7.25–7.26
- Texas tower deployment of heads, 4.39
- three-axes motion, 3.21
- tripod-deployed, 6.9, 6.10
 - and nearfield beam, 2.16
 - search patterns for body search and recovery, 8.21–8.23
- tunable-frequency 3.18
- for underwater imaging, 3.7–3.62
 - introduction to, 3.7–3.8, 3.12
 - system configuration of, 3.19
- universal deployment pole for profiling, 4.36
- using to locate body and other evidence, 8.7
- visualization of underwater structures, 5.5–5.43
- wet/dry diving bell deployment, 6.16
- Z-swath coverage, 4.14
- scour, 5.5
 - cause of, 4.40
- sea grass, acoustic response to frequencies, 9.13
- seabed
 - mapping of, ROV, and target geo-coding, 7.21–7.25
 - mosaic showing exposed bedrock, 9.47
 - overlapping coverage of, 5.19–5.20
 - topography of, and towfish, 9.66
 - vertical acoustic coverage with sonar adjacent to, 3.40
- search, questions specific to, 9.59
- search and survey
 - coverage grids, 9.56
 - line grid patterns, 9.55–9.56
 - mosaic requirements, 9.47
 - operational concerns, 9.48–9.70
 - size of search area, 9.59
- search area, for body search and recovery, 8.10–8.11
- search patterns
 - for body search and recovery, 8.20–8.30
 - observation-class ROV, for body search and recovery, 8.26–8.28
 - for horizontally mounted scanning sonar, 7.15
- ROV
 - scanning sonar, 7.26–7.28
 - search of steep slope, 8.32
 - without acoustic navigation, for body search and recovery, 8.29
 - tripod-deployed scanning sonar, for body search and recovery, 8.21–8.23
- second axis-drive scanning profilers, 4.54–4.57
- sector mode display, 3.8
- self-spooling gear, 9.40
- sensor packages, 9.29
- sensors, offsets between, 4.34
- serial telemetry, 2.44
- shaded response, 2.20
- shadows
 - acoustic, and diver positioning, 6.15
 - and coverage, scanning sonar, 5.26–5.43
- shafts
 - horizontal, point cloud data of, 4.55
 - large-diameter, profiles from, 4.50
 - profile of, 4.52
- shallow water, 3.9
 - deployment arrangements, 9.63
 - under-ice refraction and reverberation, 8.16
- sheet pile wall, slant range distortion on, 3.29
- ship's hull, parasitic devices on, isolating from bottom reverberation, 3.39
- shipwreck, survey with dual-axis profiler, 4.57
- shore access, and body search and recovery, 8.14–8.15
- shoreline revetment project using spreader bar deployment, 3.51
- side-scan sonar
 - augmenting diver inspection with 5.6–5.10
 - body search and recovery using, 8.5–8.36
 - bow mount frame-deployed, 9.63
 - bracket-deployed
 - visualization of bridge pier, 5.8
 - visualization of dock, 5.7
 - calculating coverage, 9.57
 - CHIRP, 9.17–9.20
 - deployed on ROVs and submersibles, 7.29–7.30
 - deployment of, set to side-scan mode, 5.8
 - displays of, 1.11
 - dual-frequency, 9.9, 9.11
 - simultaneous, 9.11–9.12
 - field operations with, 9.7–9.72
 - general, 9.42–9.47
 - system configuration for, 9.26–9.41
 - system selection for, 9.8–9.26
 - hand-deployed system, 9.27
 - high-frequency
 - body located with, 8.21
 - record showing a body, 8.6
 - Hugin 1030 fitted with HISAS, 9.25
 - instability adjacent to bridge piers, 5.9
 - interferometric (3D), 9.13–9.15
 - line turns, 9.58
 - mounted on ROVs, 7.30

- multibeam
 - pulsed CW, 9.15
 - coverage, 9.16
 - record and towfish, 9.16
- multipulse, 9.19–9.22
- navigation requirements for, 9.42
- out-of-range return, 1.44
 - geometry of, 1.43
- overview of, 1.8–1.9
- pole-mount for vertical structure visualization, 5.6
- pole-mounted interferometric, 9.13
- positioning target markers using, 8.19–8.20
- processor for, 9.26
- pulsed CW
 - multibeam, 9.15
 - range resolution, 2.32
- records with stable towfish, 5.9
- recordings, interpreting, 9.71–9.72
- relocating target position with, 9.42–9.45
- using ROVs and submersibles, 7.5–7.30
- seabed imaging coverage, 1.9
- seabed mosaic showing bedrock, 9.47
- search patterns for body search and recovery, 8.20
- and scanning sonar, comparison of sub-structure inspection, 5.11
- simultaneous dual-frequency, 9.11, 9.12
- single-beam
 - acoustic coverage, 9.8
 - vs. multipulse, 9.21
 - single-frequency, 9.8–9.11
 - speed over bottom, 9.9
- single-frequency, 9.9
- surface multipath, 1.40
- synthetic aperture, 9.22–9.26
- target identification, 9.69–9.70
 - and towfish, 9.28–9.30
 - winches for, 9.36–9.40
- side-view rigging of batwing profiler, 4.42
- signal quantization, and bit rate, 2.40
- signal transmission
 - multipulse side-scan, 9.19
 - simultaneous dual-frequency side-scan, 9.11
- simultaneous dual-frequency side-scan, 9.11–9.12
- single-beam pulsed CW scanning sonar, 3.14–3.17
- single-beam side-scan sonar
 - acoustic coverage, 9.8
 - vs. multipulse, 9.21
 - single-frequency, 9.8–9.11
 - speed over bottom, 9.9
- single-channel side-scan mode
 - deployment for operation, 3.9
 - scanning sonar in, 3.9
- single-channel, single-frequency display, 9.10
- single-frequency side-scan, 9.8–9.11
 - dual-channel display, 9.10
 - single-channel display, 9.10
- slant range
 - corrected records, 9.53
 - correction geometry, 9.52
 - distortion, 3.26–3.28
 - on sheet pile wall, 3.29
 - percentage of error, 3.30
 - and speed correction, 9.51–9.54
- slip rings, 9.39
- slope gradient, effect on first return, 3.23
- sloping structures
 - bottom, effect on calculating target height, 3.25
 - matching head geometry to, 5.15
 - scanning, 5.16
- slurry, unconsolidated, effects on profile data, 4.71
- small structures
 - vertical scans of, 5.17
 - visualization of, 5.17
- small vessel pole mounts, 4.37
- smeared returns, 3.37
- Snell's Law, 1.32, 1.36
- sonar
 - see also* imaging sonar; pulsed CW sonar; scanning sonar; side-scan sonar
 - active, diving distance from, 6.6
 - background noise check for other active, 3.56
 - basic system for, 1.8
 - directing divers using, 6.8–6.16
 - displays for, 2.36–2.38
 - fundamentals of, 1.7
 - obstacle avoidance (OAS), 7.5
 - processor for, 2.45
 - positioning, and acoustic perspective, 5.42
 - system components, 2.5–2.47
- sonar equation, 1.22–1.24
- sound, 1.10–1.17
 - attenuation in fresh water at 4°C, 1.31
 - attenuation in saltwater at 4°C, 1.32
 - other paths for, 1.45–1.46
 - speed of, 1.17–1.18, 4.24
 - effects of, 4.25
 - vs. frequency, 1.19
 - potential range errors with, 1.17
- source level, 1.22, 1.23
- specular reflector, 1.29
 - acoustic roughness targets, 1.30
- specular reflectors, multiple, body on lake bed with, 8.33
- speed
 - over bottom, single-beam, 9.9
 - correction for, 9.55
 - and slant range, 9.51–9.54
 - winch, control of, 9.38
- spokes, acoustic, due to current-induced head oscillation, 3.46
- spreader bar deployment, 3.44, 3.50, 3.52–3.53
 - to position backhoe bucket, 3.54
 - revetment project using, 3.51, 3.52

- spring tide, 4.22
- squat
 - and draft, 4.23–4.24
 - vessel, 4.24
- stabilization fin, drop-deployed cage with, 3.48
- standard foot conversion factor, 4.19
- steep slope, ROV search of, 8.32
- step size, 3.35–3.36
 - and beam pattern, vs. bottom coverage, 3.36
 - geometric effect of, 3.35
- structural deficiencies, correlating vertical and bottom scans to show, 5.23
- submarine, synthetic aperture sonar image of, 9.25
- submersibles
 - manned, cable requirements for, 7.19
 - mounting side-scan transducers on, 7.30
 - side-scan and scanning sonar, 7.5–7.30
 - side-scan deployed on, 7.29–7.30
- sub-structure inspection, comparison of side-scan and scanning sonar, 5.11
- surface float rigging, 8.28
- surface images, combining with vertical structure visualization, 5.22
- surface multipath, 1.38, 1.39
 - side-scan, 1.40
 - and thermocline-generated multipath, 1.41
- surface operation check, 3.54–3.55
- surface returns
 - and acoustic multiples, 3.43
 - and acoustic refraction due to vertical beam coverage, 3.42
 - potentially masking bottom targets, 3.42
- surface reverberation, using tilt transducer to reduce, 3.38
- surface rigging, hand deploying, 3.47
- surface targets
 - and body search and recovery, 8.15
 - background reverberation from, 1.47
- surge tower
 - dual-axis profiler deployment for, 4.54
 - point cloud data for, 4.55
- surveillance camera, 9.40
- synthetic aperture side-scan sonar, 9.22–9.26
 - vs. along-track beam coverage, 9.24
 - pipeline image, 9.26
 - processed WWII submarine image, 9.25
- system configuration, side-scan sonar, for field operations, 9.26–9.41
- system gain, setting, 3.59
- system selection, side-scan sonar, for field operations, 9.8–9.26
- tactile investigation, 1.5
- target markers
 - for body search and recovery, 8.17–8.20
 - crab traps used as, 8.18
 - positioning for scanning sonar, 8.19
 - positioning using side-scan, 8.19–8.20
 - reflective, for under-ice head orientation, 8.25
- target strength, 1.21, 1.22, 1.24
- targets
 - acoustic roughness, and specular reflector, 1.30
 - alignment of, 9.49
 - and bandwidth, 2.27
 - bent appearance of, 3.30
 - bottom vs. mid-water, establishing, 6.14
 - bottom, surface returns potentially masking, 3.42
 - composition of, 9.49
 - detection of, geometric effect of, 3.35
 - determining magnetic bearing without an integrated compass, 8.26
 - directing divers on a compass heading, 8.34
 - elongated appearance of, 3.30
 - factors contributing to position errors, 9.46
 - geo-coding of, and ROV seabed mapping, 7.21–7.25
 - geographically positioning, 9.43–9.45
 - geometric position vs. display position, 3.28
 - height of
 - effect of bottom slope in calculating, 3.25
 - variables impacting accuracy of calculation, 3.26
 - identification of, 9.69–9.70
 - interpreting, for body search and recovery, 8.30
 - legal ownership of, 9.59
 - long-range, and pulse length, 2.29
 - measurement of, effect of transducer tilt, 3.39
 - mid-water
 - 3D plot of, 4.31
 - background reverberation from, 1.47
 - and body search and recovery, 8.15
 - detection with horizontally mounted imaging sonar, 7.16
 - images of rope and flotation collar, 7.16
 - profile points generated from, 4.30
 - reverberation of biomass, 1.47
 - orientation of, and incident angle, 1.28
 - questions specific to search programs, 9.59
 - range selection and size, 9.51
 - reflectivity of, and incident angle and beam spreading, 1.29
 - relocating position with side-scan sonar, 9.42–9.45
 - resolution of, internal pipeline, 4.63
- ROV
 - equipment configuration for geo-referencing, 7.23
 - requirements for geo-referencing, 7.22
 - scanning sonar, ROV prosecution of, 7.25–7.26
 - shape and reflectivity of, 1.27
 - size and range selection, 9.51
 - size and shape, 9.49
 - small, positioning diver when prosecuting, 6.12
 - smearing of, and banded returns, 3.36
 - sound absorbing, 1.27
 - surface, and body search and recovery, 8.15
 - surface, background reverberation from, 1.47

- telemetry, 2.43–2.45
 - ARCNET, 2.44
 - Asymmetric Digital Subscriber Line (ADSL), 2.44
 - considerations for, 2.45
 - Ethernet, 2.44
 - serial, 2.44
 - speed of, 2.44
 - types of, 2.43–2.44
- terminology, for mechanically scanned profiling, 4.10–4.11
- Texas tower, 4.36
 - deployment of heads, 4.39
- thermocline, 1.41
 - refraction of, and scanning sonar, 1.35
 - thermocline-generated multipath, 1.41
- three-axes motion, scanning sonar, 3.21
- tides
 - and body search and recovery, 8.14
 - extremes of, 4.21
 - monitoring level of, 4.23
 - overview of, 4.22
- tie lines, 4.32, 4.33
- tilt transducers
 - effect of, 3.39
 - geometry of, 3.37
 - using to minimize bottom reverberation, 3.38
 - using to reduce surface reverberation, 3.38
- time-varied gain, 2.41–2.42
 - compensation of, 2.42
 - noise generated by, 3.61
 - using wrong factors, 2.43
- Toledo Bend Reservoir, complex bottom of, 8.13
- tow, two-part, 9.30
- tow cable
 - grip arrangement to secure, 9.62
 - hand-deployed side-scan, 9.27
 - soft, depth and layback position, 9.28
 - stern, hand-deployed, 9.61
- towfish
 - configuration of, 9.28
 - equipment deployment, 9.63–9.64
 - kiting, 9.35
 - and man-made hazards, 9.66
 - motion of, 9.30
 - multibeam side-scan, 9.16
 - options for side-scan, 9.29
 - pitch of, 9.31
 - effect on high- and low-frequency arrays, 9.32
 - and seabed topography, 9.66
 - stable, side-scan sonar record with, 5.9
- towing arrangements, 9.29–9.31
- transducer array, 2.14
- transducers, 2.5, 2.6–2.7
 - alignment of, and navigation receiver, 4.33
 - beam patterns of, 3.16
 - composite, 2.9–2.10
 - depression angles, 9.50
 - disc, 2.14
 - domed, scanning sonar head, 3.14
 - exposed, scanning sonar head, 3.14
 - guards for, 7.13
 - height above bottom, 6.9
 - linear, 2.14
 - mounting up/down, for ROVs, 7.7–7.9
 - overview of design, 2.7–2.11
 - position of, effect on visualizing vertical structure, 5.14
 - positioning, for ROVs, 7.12–7.14
 - protecting, for ROVs, 7.12–7.14
 - rub test and transmit pulse, 3.55
 - shape and directivity of, 2.8
 - side-scan, mounting on ROV or submersible, 7.30
 - and single face directionality, 2.8
 - tilt, 3.37–3.39
- transmission, CHIRP, 2.34
- transmission loss, 1.22, 1.23
- transmit and receive signal geometry, interferometric side-scan, 9.14
- transmit pulse, transducer rub test and, 3.55
- transmitters, 2.22–2.27
 - bandwidth, 2.23–2.26
 - effective power output, 2.23
 - pulse length, 2.27
 - selecting, 2.28
- transverse resolution, 9.9, 2.30, 2.31
 - beam coverage vs. synthetic aperture length, 9.24
 - vs. range, 4.63
- trash rack, 4.51
 - horizontal and vertical profiles of, 4.52
- trencher profile system utilizing four heads, 4.72
- trim
 - observation-class ROV, 7.11
 - vehicle, for ROVs, 7.10–7.11
- tripods
 - deployment of, 3.44, 3.45
 - with beam parallel to seabed, 3.8
 - grid patterns and overlap coverage, 8.24
 - hand deploying, 3.47
 - and head orientation, 6.10–6.11
 - directing diver to side of, 6.13
 - scanning sonar, 6.9, 6.10
 - search patterns, for body search and recovery, 8.21–8.23
- tunable-frequency scanning sonar, 3.18
- tunnels
 - horizontal, profiling, 4.58–4.65
 - profile coverage, 4.64
 - ROV profiling geometry for, 4.60
 - scanning sonar arrangement for inspection, 4.65
 - scanning sonar coverage for inspection, 4.66
- two-way beamwidth, 2.17
- umbilicals, 2.5, 2.45
 - small, clump weighting, 7.28
- under-dock profiles, 4.38
 - point cloud projection of, 4.38

- under-ice refraction, 1.36
 - shallow-water refraction and reverberation, 8.16
- underwater acoustics, overview of, 1.5–1.47
- underwater imaging
 - overview of, 1.5
 - scanning sonar for, 3.7–3.62
- underwater inspection, traditional methods of, 5.5–5.6
- underwater profiling survey basics, 4.15–4.27
- underwater structures, visualization using scanning sonar, 5.43–5.5
- units of measure, 4.19
 - acoustic, 1.20–1.22
- universal deployment pole for profiling scanning sonar, 4.36
- unshaded response, 2.20
- upstream view of batwing scan geometry, 4.43
- US engineering drawing sizes, commonly used, 5.36
- US Navy Diving Manual*, 6.6
- US Survey foot conversion factor, 4.19
- vector images
 - converting raster images to, 5.26
 - overview of, 5.25–5.27
 - vs. raster images, 5.26
- vehicle trim, for ROVs, 7.10–7.11
- vertical coverage, 3.41–3.42, 3.44
 - of 15° beam, 3.41
 - of 22° beam, 3.41
 - of 30° beam, 3.41
 - of 40° beam, 3.41
 - with sonar adjacent to seabed, 3.40
- vertical mounting
 - of imaging sonar, and orthogonally mounted sonar, 7.18
 - minimum height, 7.7
- vertical profiles of trash rack, 4.52
- vertical scans
 - and bottom scans, correlation of, 5.22–5.23
 - of small structures, 5.17
- vertical shaft
 - 3D plot of, 4.28
 - 24m-diameter, deployment arrangement to profile, 4.50
 - profiling of, 4.49–4.54
- vertical structures
 - deployment arrangements for, 5.12
 - horizontally mounted scanning sonar detailing, 3.10
 - visualization of
 - and bottom visualization, correlation of, 5.18
 - combining surface images with, 5.22
 - effect of transducer position on, 5.14
 - pole-mount side-scan for, 5.6
- vessel safety, 6.7
- visual imaging, 1.5, 1.6
- visualization
 - of bridge pier, with bracket-deployed side-scan, 5.8
 - correlation of bottom and vertical scans, 5.18
 - of dock, with bracket-deployed side-scan, 5.7
 - of small structures, 5.17
 - pile bent, 5.17
 - of underwater structures using scanning sonar, 5.5–5.43
 - vertical deployment arrangements for, 5.12
 - of vertical structures
 - combining surface images with, 5.22
 - effect of transducer position on, 5.14
 - pole-mount side-scan for, 5.6
- water, shallow, 3.9
- water column, consequence of removal, 9.54
- water current, 6.10
- water depth, 9.49–9.50
 - and body search and recovery, 8.11
 - vs. sonar range, 3.40
- water intake bays, point cloud 3D and contour plots of, 4.56
- water test, dockside, 3.55–3.57
- waterline, using to orient the sonar head, 4.49
- wavelength, 1.20
 - and frequency, 1.19
- waves
 - and body search and recovery, 8.14
 - longitudinal, 1.10, 1.12
- wet/dry diving bell scanning sonar deployment, 6.16
- winches, side-scan, 9.36–9.40
 - arrangement for, 9.36
 - cable drum brakes, 9.39
 - environmental protection, 9.39
 - line pull, 9.38
 - options for, 9.39–9.40
 - power source, 9.37–9.38
 - remote control, 9.39
 - size and weight restrictions, 9.37
 - slip rings, 9.39
 - speed control, 9.38
 - winch-deployed cables, 9.32–9.33
- wind, and body search and recovery, 8.14
- work-class ROV, imaging sonar mounted on, 7.14
- worksite, monitoring, 6.8
- WWII submarine, processed synthetic aperture sonar image of, 9.25
- XY grids, absolute and relative, 4.17–4.18
- XYZ, roll, yaw, and pitch orientation, 4.18
- yaw, 3.21–3.22 , 4.26–4.27
 - and pitch and roll alignment, 4.46–4.48
 - and roll, pitch, and XYZ orientation, 4.18
- ZOOM display, 2.37
- Z-swath, 4.29
 - coverage with scanning sonar, 4.14
 - processed data, 4.14

ABOUT THE AUTHOR

With a background in commercial explosives and diving, underwater photography and sonar, Atherton worked for and came to manage the Offshore Survey Division of CAN-DIVE Services Ltd., an internationally affiliated, commercial diving company in North Vancouver, British Columbia. The job took him worldwide for 16 years on a diversity of undersea challenges. WWII bomb recovery in Trinidad, deep-water pipeline route surveys, cable-lay operations, locating and recovering aircraft, ships and bodies, and working on underwater television and movie documentaries were all part of the business.

In 1991, Atherton was asked to join Simrad Mesotech Ltd. (now Kongsberg Mesotech Ltd.) where he remains involved in all aspects of sonar system development, testing, applications, operations and another passion—teaching operational underwater acoustics.

Atherton is a frequent guest lecturer at universities, colleges, international marine and security conferences, and private and governmental in-house training seminars. Having “been there, done that,” he brings to these presentations, and to *Echoes and Images*, *The Encyclopedia of Side-Scan and Scanning Sonar Operations*, tried and true perspectives of what it takes to get an underwater search or survey job done, and to make sure it’s done *right*.

Mark is married to his best friend and editor, Jane Lynn Atherton, and lives in Vancouver, British Columbia, Canada.

Published by OysterInk Publications, Vancouver, BC, Canada

To order

Echoes and Images,

The Encyclopedia of Side-Scan and Scanning Sonar Operations,

go to www.echoesandimages.com

or contact info@echoesandimages.com.